

SKU.1 CG-S 4x1.5A circuit switching

DualGuard-S – central battery system

SKU.1 CG-S 4x1.5A



SKU.1 CG-S 4x1.5A

- CG technology provides for automatic monitoring of up to 20 safety lights and emergency signs without requiring the transmission of additional data for each circuit
- Overload indicator
- Programmable switching for each individual light with no need to make adjustment directly to the light itself
- Automated isolation fault finding
- Assemblies use service-friendly module technology, wired ready for connection to triple-deck 4 mm² neutral terminals
- Large finger-safe ventilation slits for optimum heat dissipation
- Simple, time-saving snap-on click installation on device rack
- Wide sign racks for customized labeling
- Meets all EMV requirements for industrial and commercial use
- DEKRA system certification documents product quality and compliance with standards for the entire system
- Functionality for 30 minutes during fire verified in a fire test conducted by an independent materials testing institute
- Conforms to RoHS and REACH

Inputs

Nominal AC voltage 220-240V

Nominal DC voltage 184-275V

Rated frequency 50 or 60 Hz

Maximum head dissipation capacity: 8 W

Outputs

Rated current 1.5A

short-circuit current 1500A

Inrush current 60A per circuit/240A per module

Net system TN SKU.1 CG-S 4x1.5A

Net system IT SKU.1 CG-S 4x1.5A IT

SKU.1 CG-S 4x1.5A IT



Order details

Model	Included with delivery	Order no.
SKU.1 CG-S 4 x 1.5A	Circuit switching 4 x 1.5A for component rack installation	40071361550
SKU.1 CG-S 4 x 1.5A IT	Circuit switching 4 x 1.5A for component rack installation in IT net systems	40071361555