



## LED damp-proof light fitting

**161 12L42 T40 H55**

[ Item no. : 16117 0502 ]

**General product description**


Sturdy LED damp-proof light fitting for high ambient temperatures and wide temperature ranges. Highly impact-resistant glass fibre reinforced polyester housing and frosted diffuser with high impact resistance. Captive clips, multi-part, incl. two safety clips, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection.

**General product benefits**

- perfect solution for application with very high ambient temperatures and extreme ambient temperature fluctuations
- sturdy, extremely reliable high-quality light fitting for application in rough industrial environments
- high impact resistant housing, chemical and UV resistant
- diffuser with high mechanical resistance
- highly efficient by using high-quality ECG and LED modules
- homogenous illumination due to frosted diffuser, comfortable perception of light and brilliant glare limitation
- sustainable, interchangeable components
- future proof by using standardised Zhaga LED modules

**Applications**

Humid, wet and dusty indoor areas and sheltered outdoor areas in commerce, trade and industry etc., areas with wide ambient temperature ranges, e.g. climatic chambers, material containers, test stands, regions with extreme temperature changes etc., areas with high ambient temperatures



## LED damp-proof light fitting

**161 12L42 T40 H55****[ Item no. : 16117 0502 ]****Technical data****Key technical data**

Light source:	LED
LED module standard:	Zhaga
Exchangeability:	light source and control gear replaceable by qualified person
Connected load:	27 W
Luminaire luminous flux:	4240 lm
Luminous efficacy:	157 lm/W
Colour temperature:	4000 K
Colour rendering (CRI):	≥ 80
Light colour:	840
Admissible ambient temperature Ta:	-40 °C to +55 °C
Control gear:	1 x ECG, Overload protection, Short circuit protection

**Lighting technology**

Light distribution:	symmetrical wide beam
Beam angle:	120 °
Photobiological safety:	RG0

**Service life**

Service life LED:	L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25° C)
-------------------	---

**Electrical connection**

Rated voltage:	220 - 240 V, 50/60 Hz
Terminal clamp:	Cage clamp, 3-polig, 0.75 - 2.5 mm <sup>2</sup>
Max. no. (with CB B16):	32
CB B10/B13/B20:	21/26/41
CB C10/C13/C16/C20:	33/43/54/66
Cable entries:	M20 (2x), blanking plug (2x), Plastic, 8 - 15 mm

**Housing**

Housing material:	Glass fibre reinforced polyester
Colour:	grey

**Cover**

Cover type/material:	Diffuser (PC)
Cover characteristic:	satined
Closure:	Clips (Plastic)

**Mounting**

Mounting method (accessories possibly needed):	Ceiling, Wall, Ceiling with bracket, Ceiling with angle, Suspended, Mounting rail, Wall with bracket, Wall with angle
--	---

**Mounting**

Operating position:	downwards radiation, forwards radiation, horizontal
Mounting:	2-point

**Features/Certificates**

Protection class:	I
IP rating:	IP65
IK rating:	IK09
Limited surface temperature:	D
Approval marks:	CE
Energy efficiency class:	C

**Dimension/Weight**

Length:	1272.00 mm
Width/Diameter:	116.00 mm
Height:	125.00 mm
Net weight:	3.10 kg
EAN/GTIN:	4041254278445

## LED damp-proof light fitting

**161 12L42 T40 H55**

[ Item no. : 16117 0502 ]

**Optional accessories/spare parts**

Item no.	Item name	Item description
16111 9035	ABD 161 018 F	cover PMMA frosted
16111 9031	ABD 161 036 F	cover PMMA frosted
16111 9032	ABD 161 058 F	cover PMMA frosted
16111 9036	ABD 161 018 F PC	cover PC frosted
16111 9033	ABD 161 036 F PC	cover PC frosted
16111 9034	ABD 161 058 F PC	cover PC frosted
16111 9017	ABD 161 018 LM	cover high chemical resistant clear IFS
16111 9018	ABD 161 036 LM	cover high chemical resistant clear IFS
16111 9019	ABD 161 058 LM	cover high chemical resistant clear IFS
90004 0001	SK 120	wire guard powder coated for 161 06..
90004 0002	SK 140	wire guard powder coated for 161 12..
90004 0003	SK 165	wire guard powder coated for 161 15..
90053 9008	KK/KKS FR VE10	locking clips (10 pcs.) with 2 safety clips
90055 9004	KE/KES VE10	locking clips (10 pcs.) with 2 safety clips
90053 9004	KKS P	safety clips (1 pair)
90055 9005	KES P	safety clips (1 pair)
90063 9000	2511	blanking plug M20
25610 9000	2561	cable gland M20
25600 9000	2560	cable gland M25
90259 9002	DAE20	breather M20
90259 9003	DAE20/25	breather M20 with extension M25
90093 0002	183 RO 112 A P	2 pipe clamps 1 1/2", stainless steel, with support
90094 0002	183 RO 2 A P	2 pipe clamps 2", stainless steel, with support
90045 9001	HW 30 P BR 161/2 163/4 175/6	2 brackets aluminium 30°
90045 9002	HW 45 P BR 161/2 163/4 175/6	2 brackets aluminium 45°
90045 9004	HW 60 P BR 161/2 163/4 175/6	2 brackets aluminium 60°
90045 9003	HW 90 P BR 161/2 163/4 175/6	2 brackets aluminium 90°
90049 0002	183 S	hook stainless steel for chain mounting
90095 0001	183 DS	bracket stainless steel with screw M5